

TRAMFLOC, INC.

6046 FM 2920 Road, #615, Spring, TX 77379 Voice: 888-929-8973 Fax: 480-383-6895

Technical Information Bulletin

TRAMFLOC® 1040 TABLET FLOCCULANT

Product Description

Tramfloc® 1040 tablet flocculant is a fast release anionic, granular polyacrylamide polymer of very high molecular weight produced as an effervescent tablet. Tramfloc® 1040 is completely water soluble and safe to apply. Tramfloc® 1040 is used to control erosion in agricultural fields, on river banks, on construction slopes, to precipitate solids in muddy water bodies, mineral slurries, mine tailings, and in marble and granite cutting.

Additional Use Information

Tramfloc® 1040 is designed to dissolve immediately upon contact with water. The product is also used in water clarification and infiltration applications. Tramfloc® 1040 will viscosify water and flocculate fine soil particles, mud, clays and silt rapidly. Tramfloc® 1040 is also applied as a soil conditioner to control soil erosion and application rates with vary with soil type, field slope and water volume in the head ditch.

Mixing and Dosage

For settling of soil fines, mineral fines or general debris, Tramfloc® 1040 should be dosed at the rate of one tablet to 250 gallons of water will produce a 5 ppm dosage. The product mixes evenly with proper agitation of < 400 rpm and is quite stable. The tablet is of particular importance where capital intensive polymer make down equipment would be impractical to install.

Packaging

Tramfloc® 1040 is available in 44# net weight pails, packed 32 pails/pallet. Each tablet weighs 50 grams.

Handling and Storage

Handle all industrial chemicals with care and consult the material safety data sheet before product use. Tramfloc® 1040 should be stored in a cool, dry place for up to one year.

Safety and Health

Spills of polymer are extremely slippery. Precautions should be taken to prevent them from entering lakes or streams. Tramfloc® Polymer Cleaner 348 can be used to remove residue from equipment and floors. Polymer can be flushed with copious amounts of water and disposed of according to local regulations or treated with an absorbent material, then collected for subsequent legal disposal. Tramfloc® 1040 has been shown to exhibit a low order of toxicity. Nevertheless, precautions should be taken to prevent inhalation, ingestion or contact with skin or eyes. Observing basic industrial hygiene precautions should prevent any health or safety hazards.

The above data is based upon information Tramfloc, Inc. believes reliable and is supplied for informational purposes only. Tramfloc, Inc. disclaims any liability for damage or injury which results from the use of the above data and nothing contained herein shall constitute a guarantee, warranty (including warranty of merchantability or fitness for a particular purpose) or representation (including freedom from patent liability) by Tramfloc, Inc. with respect to the accuracy or completeness of the data, the product described, or their use for any specific purpose even if that purpose is known to Tramfloc, Inc. The final determination of the suitability of the information, the manner of use of the information or product and potential infringement of patents is the sole responsibility of the user.