

TRAMFLOC, INC.

P. O. Box 350, Tempe, AZ 85280-0350 Voice: 480-491-6895 Fax: 480-456-1664

Technical Information Bulletin

TRAMFLOC® 1118 DEFOAMER/ANTIFOAM

Product Description

Tramfloc® 1118 is a 60% active silicone emulsion and nonionic emulsifier with excellent stability and performance efficacy in many waste and process applications where foaming conditions and blankets should be avoided. This Tramfloc formulation is manufactured under strictly sanitary conditions and uses high quality food grade feed stocks. This product is carefully formulated so that it resists degradation. Tramfloc® 1118 is completely water soluble and should be applied wherever foam presents an esthetic or operational problem or regulatory violation possibility.

Uses

Tramfloc® 1118 effectively disperses foam columns and blankets without producing a sheen of the reagent on the process flow or wastewater outfall surface. The correct application of Tramfloc® 1118 can result in more effective operation of laser, ultrasonic, and mechanically operated level devices, more pleasing esthetic conditions, better visibility of reaction vessel activity, reduced fouling, reduced cay-over of total suspended solids, and cleaner systems. Tramfloc® 1118 is in compliance with 21 CFR 176.200-10 and 40 CFR 180.1001. The formulation is a very stable product, yet it releases its silicone very rapidly when charged to the foaming media.

Feeding

It is recommended that the product be fed continuously at a low dosage to a point in the system prior to the generation of the foaming condition. The foam preventive activity of Tramfloc® 1118 will allow for the most economical dosage. The formulation is stable in acidic, neutral and alkaline aqueous systems.

Packaging

Tramfloc® 1118 is available in 460# net weight drums, 2600# tote bins, tank wagons and, rail cars.

Handling and Storage

Closed containers of Tramfloc® 1118 store well for six months in a cool, dry place.

Safety and Health

Spills of this chemical are slippery. Precautions should be taken to prevent them from entering lakes or streams. Chemical can be flushed with copious amounts of water and disposed of according to local regulations or treated with an absorbent material, then collected for subsequent legal disposal. Always wear protective safety equipment and prevent contact of chemical with skins, eyes, and clothing. Observing basic industrial hygiene precautions should prevent any health or safety hazards.

The above data is based upon information Tramfloc, Inc. believes reliable and is supplied for informational purposes only. Tramfloc, Inc. disclaims any liability for damage or injury which results from the use of the above data and nothing contained herein shall constitute a guarantee, warranty (including warranty of merchantability or fitness for a particular purpose) or representation (including freedom from patent liability) by Tramfloc, Inc. with respect to the accuracy or completeness of the data, the product described, or their use for any specific purpose even if that purpose is known to Tramfloc, Inc. The final determination of the suitability of the information, the manner of use of the information or product and potential infringement of patents is the sole responsibility of the user.