

TRAMFLOC, INC.

P. O. Box 350, Tempe, AZ 85280-0350 Voice: 480-491-6895 Fax: 480-456-1664

Technical Information Bulletin

TRAMFLOC[®] 1125 ANTIFOAM

Product Type	General Purpose Industrial Foam Control Agent	
Product Description	TRAMFLOC [®] 1125 is a general purpose, long-lasting, non-silicone, fisheye-free antifoam especially effective in water-reducible coatings. TRAMFLOC [®] 1125 allows the formulator to use a defoaming agent without the unwanted side-effects usually associated with defoamers. TRAMFLOC [®] 1125 is effective over a wide pH and temperature range. Long-lasting foam control is produced without film imperfections such as orange peel and fisheyes. Color acceptance in pigmented coatings is generally excellent.	
Typical Properties	Appearance	Tan opaque liquid
	Viscosity (mPa-s)	1750
	Density (kg/L)	0.880
	Flash Point (°C)	120
Typical Applications	<ul style="list-style-type: none">• Latex paints and coatings• Emulsion polymerization• Water-based inks and coatings• Acrylic and latex emulsions• Adhesives and glues	
Addition Levels	For latex coatings the recommended addition level for TRAMFLOC [®] 1125 is 2-5 pounds per 100 gal of paint. One-half the amount is added with the pigment prior to grinding and one-half in the letdown portion. For water-reducible coatings, the recommended addition level is 0.1 to 2.5%, based upon total formulation weight.	
Incorporation	TRAMFLOC [®] 1125 can be used as received or by prediluting with water. Dilutions should be stirred until ready for use.	
Responsible Care	For complete safety, health, personnel protection and first aid information, refer to the Material Safety Data Sheet (MSDS).	

The above data is based upon information Tramfloc, Inc. believes reliable and is supplied for informational purposes only. Tramfloc, Inc. disclaims any liability for damage or injury which results from the use of the above data and nothing contained herein shall constitute a guarantee, warranty (including warranty of merchantability or fitness for a particular purpose) or representation (including freedom from patent liability) by Tramfloc, Inc. with respect to the accuracy or completeness of the data, the product described, or their use for any specific purpose even if that purpose is known to Tramfloc, Inc. The final determination of the suitability of the information, the manner of use of the information or product and potential infringement of patents is the sole responsibility of the user.

Emerald Foam Control, LLC
195 Brooks Blvd.
Spartanburg, SC 29307
Tel: 1-307-634-7699
Fax: 1-307-634-8319

Emerald Foam Control, LLC
311 Cleveland Place
Cheyenne, WY 82007
Tel: 1-307-634-7699
Fax: 1-307-634-8319

Emerald Foam Control, LLC
Billbrookdeich 157
22113 Hamburg, Germany
Tel: +49 40 7310-9765
Fax: +49 40 7310-9779

Emerald Foam Control, LLC
Av. Fagundes Filho, 77
12 Andar Conj. 124 Sao Judas
04304-010 Sao Paulo, Brazil
Tel: +55 11 5585 3719
Fax: +55 11 5581 8201

Visit our website www.emeraldmaterials.com