

# TRAMFLOC, INC.

6046 FM 2920 Road #615, Spring, TX 77379    Voice: 888-929-8973    Fax: 480-383-6895

## Technical Information Bulletin

### TRAMFLOC® 129 LOG FLOCCULANT

#### ***Product Description***

Tramfloc® 129 LOG is an anionic polyacrylamide of medium molecular weight and moderate charge density formed into a logs for moderately slow dissolving in various applications. Tramfloc® 129 LOG is completely water soluble and produces high viscosity solutions at very low concentrations. Tramfloc® 129 LOG is used as a general flocculant.

#### ***Uses***

Tramfloc® 129 LOG is used as a floc builder and after the addition of poly DADMAC or epiamine coagulants and is used alone or with primary coagulants for clarification, DAF/IAF, mineral applications, and phosphate and multivalent metal salt removal. Tramfloc® 129 LOG is used wherever the application of emulsion or granular flocculants is contraindicated by remote access, power, labor or capital constraints.

#### ***Make-Down***

It is recommended that mesh bags be placed into water flows and streams from pivots, ponds and lagoons.

#### ***Packaging***

Tramfloc® 129 LOG is available in 5# blocks and packed eight blocks per case and 12 cases/pallet.

#### ***Handling and Storage***

Polymer solutions should be made-down and diluted in stainless steel, FRP or plastic vessels. Amphoteric metallic components should be avoided. Make-down water temperatures should be between 40-145° F. Unopened bags are hygroscopic and should be stored in a cool, dry place.

#### ***Safety and Health***

Dry polymer spills should be left dry and swept up at once. Spills of solutions are extremely slippery. Precautions should be taken to prevent them from entering lakes or streams. Tramfloc® Polymer Cleaner 348 can be used to remove residue from equipment and floors. Polymer can be flushed with copious amounts of water and disposed of according to local regulations or treated with an absorbent material, then collected for subsequent legal disposal. Tramfloc® 129 LOG has been shown to exhibit a low order of toxicity. Nevertheless, precaution should be taken to prevent inhalation, ingestion or contact with skin or eyes. Observing basic industrial hygiene precautions should prevent any health or safety hazards.

The above data is based upon information Tramfloc, Inc. believes reliable and is supplied for informational purposes only. Tramfloc, Inc. disclaims any liability for damage or injury which results from the use of the above data and nothing contained herein shall constitute a guarantee, warranty (including warranty of merchantability or fitness for a particular purpose) or representation (including freedom from patent liability) by Tramfloc, Inc. with respect to the accuracy or completeness of the data, the product described, or their use for any specific purpose even if that purpose is known to Tramfloc, Inc. The final determination of the suitability of the information, the manner of use of the information or product and potential infringement of patents is the sole responsibility of the user.