

TRAMFLOC, INC.

P. O. Box 350      Tempe, AZ 85280-0350      Voice: 480-491-6895      Fax: 480-456-1664

Technical Information Bulletin

TRAMFLOC® 400 B, 400 C CATIONIC FLOCCULANTS

***Product Description***

Tramfloc® 400B, 400C are a medium charge and high weight cationic polyacrylamide formulations. Tramfloc® 400 B, 400 C are supplied as a granular powder. Tramfloc® 400B, 400C are completely water soluble and produces high viscosity solutions at very low concentrations. Tramfloc® 400B, 400C are is used as a general flocculant and dewatering agents in municipal operations, tailings thickeners and in various industrial applications.

***Uses***

Tramfloc® 400B, 400C can be used for conditioning primary and secondary, digested sludge and to aid in dewatering. Tramfloc® 400B, 400C are used alone or with primary coagulants.

***Make-Down***

It is recommended that stock solutions, 0.2-0.5%, be prepared from which feed solutions, 0.05-0.1%, are then made.

***Packaging***

Tramfloc® 400B, 400C are available in 55# triple walled bags packed 40 per pallet and in SuperSaks™.

***Handling and Storage***

Polymer solutions should be made-down and diluted in stainless steel, FRP or plastic vessels. Amphoteric metallic components should be avoided. Make-down water temperatures should be between 60-85<sup>0</sup> F. Unopened bags are hygroscopic and should be stored in a cool, dry place.

***Safety and Health***

Dry polymer spills should be left dry and swept up at once. Spills of solutions are extremely slippery. Precautions should be taken to prevent them from entering lakes or streams. Tramfloc® Polymer Cleaner 348 can be used to remove residue from equipment and floors. Polymer can be flushed with copious amounts of water and disposed of according to local regulations or treated with an absorbent material, then collected for subsequent legal disposal. Tramfloc® 400B, 400C have been shown to exhibit a low order of toxicity. Nevertheless, precaution should be taken to prevent inhalation, ingestion or contact with skin or eyes. Observing basic industrial hygiene precautions should prevent any health or safety hazards.

The above data is based upon information Tramfloc, Inc. believes reliable and is supplied for informational purposes only. Tramfloc, Inc. disclaims any liability for damage or injury which results from the use of the above data and nothing contained herein shall constitute a guarantee, warranty (including warranty of merchantability or fitness for a particular purpose) or representation (including freedom from patent liability) by Tramfloc, Inc. with respect to the accuracy or completeness of the data, the product described, or their use for any specific purpose even if that purpose is known to Tramfloc, Inc. The final determination of the suitability of the information, the manner of use of the information or product and potential infringement of patents is the sole responsibility of the user.