

TRAMFLOC, INC.

6046 FM 2920 Road, Spring, TX 77379 Voice: 888-929-8973 Fax: 480-383-6895

Technical Information Bulletin

TRAMFLOC® 1113 FERMENTATION ANTIFOAM

Product Description

Tramfloc® 1113 is formulated for use in fermentation and yeast propagation. It is a 100% active product and should be used as received without dilution.

Usage

Tramfloc® 1113 is made from ingredients which are approved for use in foods as specified by the Code of Federal Regulations: Title 21, Section 173.340. Tramfloc® 1113 should be fed directly to the fermenters and or yeast propagation tank. The optimum use level must be determined experimentally and will vary with the severity of the foaming problem. The suggested starting rate is 100 PPM of the feed. The feed rate can then be optimized based on the fermenter conditions.

Typical Properties

Appearance at 25° C	White/Off-White Opaque Liquid
Specific Gravity at 25° C	0.94
Density (Lbs./U.S. Gallons)	7.8
Solubility in Water	Emulsifies

Packaging

Tramfloc® 1113 is available in 55 gallon drums, 330 gallon totes and in bulk quantities.

The above data is based upon information Tramfloc, Inc. believes reliable and is supplied for informational purposes only. Tramfloc, Inc. disclaims any liability for damage or injury which results from the use of the above data and nothing contained herein shall constitute a guarantee, warranty (including warranty of merchantability or fitness for a particular purpose) or representation (including freedom from patent liability) by Tramfloc, Inc. with respect to the accuracy or completeness of the data, the product described, or their use for any specific purpose even if that purpose is known to Tramfloc, Inc. The final determination of the suitability of the information, the manner of use of the information or product and potential infringement of patents is the sole responsibility of the user.