

TRAMFLOC, INC.

6046 FM 2920 Road, Spring, TX 77379 Voice: 888-929-8973 Fax: 480-383-6895

Technical Information Bulletin

TRAMFLOC® 1132 FOAM CONTROL AGENT

TRAMFLOC® 1132 meets the requirements of the Code of Federal Regulations: Title 21, Section 173.340 and complies with monograph on Simethicone of the National Formulary XIV.

TYPICAL PROPERTIES:

Appearance	Translucent grey liquid
Specific Gravity at 25° C	0.98
Refractive Index	1.400 – 1.410
Arsenic	< 0.0003%
Heavy Metals	< 0.001%
Silicone Dioxide	4.0% - 4.5%
Flash Point	> 600° F
Solubility	Insoluble in water

TRAMFLOC® 1132 is available in 55-gallon non-returnable steel drums, 330-gallon non-returnable fiber totes, and in bulk.

Safety and Health

Spills of chemicals are extremely slippery. Precautions should be taken to prevent them from entering lakes or streams. Chemical can be absorbed with approved material and disposed of according to local regulations, then collected for subsequent legal disposal. Precautions should be taken to prevent inhalation, ingestion or contact with skin or eyes. Observing basic industrial hygiene precautions should prevent any health or safety hazards.

SEQ CHAPTER \h \r 1 The above data is based upon information Tramfloc, Inc. believes reliable and is supplied for informational purposes only. Tramfloc, Inc. disclaims any liability for damage or injury which results from the use of the above data and nothing contained herein shall constitute a guarantee, warranty (including warranty of merchantability or fitness for a particular purpose) or representation (including freedom from patent liability) by Tramfloc, Inc. with respect to the accuracy or completeness of the data, the product described, or their use for any specific purpose even if that purpose is known to Tramfloc, Inc. The final determination of the suitability of the information, the manner of use of the information or product and potential infringement of patents is the sole responsibility of the user.