

# TRAMFLOC, INC.

6046 FM 2920 Road, Spring, TX 77379    Voice: 888-929-8973    Fax: 480-383-6895

## Technical Information Bulletin

### TRAMFLOC® 1135 FOAM CONTROL AGENT

TRAMFLOC® 1135 is formulated for use in latex stripping. It is emulsifiable and free from large particles which can cause coagulation. It is also effective in coatings and adhesives based on emulsion polymers. Dosage of 0.2% - 0.5 % of the formulation are suggested as a starting point in evaluation.

TRAMFLOC® 1135 complies with the Code of Federal Regulations Title 21, paragraphs 175.105, 175.300, 176.170, 176.180, and 176.210. It may be used in paper and adhesives in contact with food.

#### TYPICAL PROPERTIES

|                           |                          |
|---------------------------|--------------------------|
| Appearance                | Translucent amber liquid |
| Density in U.S. Gallons   | 7.5 Lbs.                 |
| Specific Gravity at 25° C | 0.905                    |
| Solubility                | Emulsifies in Water      |

TRAMFLOC® 1135 is available in 55-gallon non-returnable steel drums, in 330-gallon non-returnable fiber totes and in bulk quantities.

Non Warranty: The data and statements contained herein are based on our research and/or the research of others, and are believed to be accurate. No guarantee of the accuracy is made however, and unless expressly stated in a written contract, the product(s) discussed herein are sold without conditions or warranties, expressed or implied. Purchasers are advised to make their own tests to determine the suitability of this product for their particular purposes. Nothing contained herein shall be construed as recommendation to use or license to operate under or to infringe on any existing patent.