

TRAMFLOC, INC.

P. O. Box 350, Tempe, AZ 85280-0350 Voice: 480-491-6895 Fax: 480-456-1664

Technical Information Bulletin

TRAMFLOC® 1177 FOAM CONTROL AGENT

Product Description

Tramfloc® 1177 is a food-grade aqueous emulsion defoamer designed to control foam in various food processes especially brewing. Tramfloc® 1177 complies with 21 CFR 173.340 (a) (1) and (2). According to this regulation, different foods have specific limitations. Tramfloc® 1177 was specifically designed to be used in food systems which experience foam formation due the presence of fats, oils, protein, sugars and other process ingredients. Tramfloc® 1177 is certified as Kosher and Pareve. There are no animal products used to manufacture of Tramfloc® 1177. Ingredients are approved vegetable based active agents, vegetable oils, and silica. This formulation is useful in controlling foam in food systems at relatively low rates.

Properties

Tramfloc® 1177 has an appearance of an opaque, pale amber liquid. It is dispersable in water and has a density of 7.68 lbs. per gallon. The formulation's flash point is >400° F.

Uses

Tramfloc® 1177 is used for the following applications: potato processing, starch recovery, sugar processing, beer brewing, and vegetable processing. Stirring is recommended prior to use of this product. In the production of foods, a starting dose of 80 ppm is recommended. The dosage should be adjusted to achieve the desired level of foam control. It is recommended that the maximum use level of Tramfloc® 1177 in processed foods should not exceed that which is deemed necessary to control foam in the process. Tramfloc® 1177 should be added neat via metering system directly to the foaming medium at a point prior to foam generation. Tramfloc® 1177 is used in whey evaporators while the formulation promotes wetting of the evaporator's surfaces and flow of the concentrated whey as it increases in solids. This results in less fouling of the surfaces, more efficient evaporation and cleaner evaporator surfaces.

Safety and Health

Wash exposed areas with soap and water. Flush eyes with water for a minimum of 15 minutes. If irritation or nausea persists, seek medical attention. If inhalation occurs, move victim to fresh air. If unconscious, administer artificial respiration and seek medical attention.

Packaging

Tramfloc® 1177 is available in 410# drums, 2500# fiber totes, tank wagons and tank cars.

The above data is based upon information Tramfloc, Inc. believes reliable and is supplied for informational purposes only. Tramfloc, Inc. disclaims any liability for damage or injury which results from the use of the above data and nothing contained herein shall constitute a guarantee, warranty (including warranty of merchantability or fitness for a particular purpose) or representation (including freedom from patent liability) by Tramfloc, Inc. with respect to the accuracy or completeness of the data, the product described, or their use for any specific purpose even if that purpose is known to Tramfloc, Inc. The final determination of the suitability of the information, the manner of use of the information or product and potential infringement of patents is the sole responsibility of the user.