# TRAMFLOC, INC.

6046 FM 2920 Road, #615, Spring, TX 77379 Voice: 888-929-8973 Fax: 480-383-6895

# **Technical Information Bulletin**

#### TRAMFLOC® 129 ANIONIC FLOCCULANT FOR SUGAR CANE JUICE

## **Product Description**

Tramfloc<sup>®</sup> 129 is a high molecular weight anionic polyacrylamide. Tramfloc<sup>®</sup> 129 is supplied as a granular powder and is completely water soluble and produces high viscosity solutions at very low concentrations. Tramfloc<sup>®</sup> 129 is NSF<sup>®</sup> approved for potable water treatment and certified organic for sugar cane and beet juice clarification.

#### Uses

Tramfloc<sup>®</sup> 129 is made from a USDA food grade material and is used as a floc builder and after the addition of polydadmac or epiamine coagulants. Tramfloc<sup>®</sup> 129 is used alone or with primary coagulants for DAF/IAF, cane mill, food plant and juice filtering, clarification and dewatering applications. Tramfloc<sup>®</sup> 129 deals effectively with differing conditions of soil, climate, sunshine and rainfall.

#### Make-Down

It is recommended that stock solutions, 0.2-0.5%, be prepared from which feed solutions, 0.05-0.1%, are then made. Tramfloc<sup>®</sup> 129 is potable water grade.

### **Packaging**

Tramfloc® 129 is available in 55.1# triple walled sacks packed 40 per pallet and in SuperSaks<sup>TM</sup>.

#### Handling and Storage

Polymer solutions should be made-down and diluted in stainless steel, FRP or plastic vessels. Amphoteric metallic components should be avoided. Make-down water temperatures should be between 60-85° F. Unopened bags are hygroscopic and should be stored in a cool, dry place.

#### Safety and Health

Animal tests have shown that Tramfloc<sup>®</sup> 129 is considered to be practically non-toxic. Dry polymer spills should be left dry and swept up at once. Spills of solutions are extremely slippery. Precautions should be taken to prevent them from entering lakes or streams. Tramfloc<sup>®</sup> Polymer Cleaner 348 can be used to remove residue from equipment and floors. Polymer can be flushed with copious amounts of water and disposed of according to local regulations or treated with an absorbent material, then collected for subsequent legal disposal. Precaution should be taken to prevent inhalation, ingestion or contact with skin or eyes. Observing basic industrial hygiene precautions should prevent any health or safety hazards.

The above data is based upon information Tramfloc, Inc. believes reliable and is supplied for informational purposes only. Tramfloc, Inc. disclaims any liability for damage or injury which results from the use of the above data and nothing contained herein shall constitute a guarantee, warranty (including warranty of merchantability or fitness for a particular purpose) or representation (including freedom from patent liability) by Tramfloc, Inc. with respect to the accuracy or completeness of the data, the product described, or their use for any specific purpose even if that purpose is known to Tramfloc, Inc. The final determination of the suitability of the information, the manner of use of the information or product and potential infringement of patents is the sole responsibility of the user.