

TRAMFLOC, INC.

6046 FM 2920 #615, Spring, TX 77379

Voice: 888-929-8973

Fax: 480-383-6895

Technical Information Bulletin

TRAMFLOC® 227 GRANULAR CATIONIC FLOCCULANT

Product Description

Tramfloc® 227 is a highly charged and high molecular weight cationic polyacrylamide formulation. Tramfloc® 227 is supplied as a granular powder. Tramfloc® 227 is completely water soluble and produces high viscosity solutions at very low concentrations. Tramfloc® 227 is used as a general flocculant and dewatering agent in municipal operations, tailings thickeners and in various industrial applications.

Uses

Tramfloc® 227 is especially formulated for drilling fluid dewatering and clarification where fresh water, light or heavy brines are generated. Tramfloc® 227 can be used also for conditioning primary and secondary, digested sludge and to aid in dewatering. Tramfloc® 227 is used alone or with primary coagulants.

Make-Down

It is recommended that stock solutions, 0.2-0.5%, be prepared from which feed solutions, 0.05-0.1%, are then made.

Packaging

Tramfloc® 227 is available in 55# triple walled bags packed 40 per pallet.

Handling and Storage

Polymer solutions should be made-down and diluted in stainless steel, FRP or plastic vessels. Amphoteric metallic components should be avoided. Make-down water temperatures should be between 60-85° F. Unopened bags are hygroscopic and should be stored in a cool, dry place.

Safety and Health

Dry polymer spills should be left dry and swept up at once. Spills of solutions are extremely slippery. Precautions should be taken to prevent them from entering lakes or streams. Polymer can be flushed with copious amounts of water and disposed of according to local regulations or treated with an absorbent material, then collected for subsequent legal disposal. Tramfloc® 227 has been shown to exhibit a low order of toxicity. Nevertheless, precaution should be taken to prevent inhalation, ingestion or contact with skin or eyes. Observing basic industrial hygiene precautions should prevent any health or safety hazards.

The above data is based upon information Tramfloc, Inc. believes reliable and is supplied for informational purposes only. Tramfloc, Inc. disclaims any liability for damage or injury which results from the use of the above data and nothing contained herein shall constitute a guarantee, warranty (including warranty of merchantability or fitness for a particular purpose) or representation (including freedom from patent liability) by Tramfloc, Inc. with respect to the accuracy or completeness of the data, the product described, or their use for any specific purpose even if that purpose is known to Tramfloc, Inc. The final determination of the suitability of the information, the manner of use of the information or product and potential infringement of patents is the sole responsibility of the user.